# Technical data sheet

## Push-fit plug Delta-Push® for pushing in

## Item number: 2351670

Push-fit plug Delta-Push® for mounting electrical installations. Suitable for concrete, calcareous limestone, full brick, hollow brick and porous concrete. Toolless mounting by pushing into a drill hole in a wall or on a ceiling. Without screws. To install cable trunking or labelling panels, for example.

HALOGEN FREE Ø6

PA Polyamide

### Master data

| | |
|---|---|
| Item number | 2351670 |
| Type | DP D 30 |
| Description 1 | Push-fit plug |
| Description 2 | for pressing in |
| Available from | 01.02.2025 |
| Manufacturer | OBO |
| Dimension | 34,2x14,2x12,2 |
| Material | Polyamide |
| Smallest sales unit | 100 |
| Unit of quantity | Piece |
| Weight | 0.083 kg |
| Weight unit | kg/100 pc. |

# Technical data sheet

## Push-fit plug Delta-Push® for pushing in

## Item number: 2351670

### Dimensions




| | |
|---|---|
| Length | 30 mm |

### Technical data

| | |
|---|---|
| Version for | Push-fit anchor |
| Drill hole depth | 35 mm |
| Drill hole diameter, max. | 6 mm |
| Drill hole diameter, min. | 6 mm |
| Suitable for fastening with cable ties | no |
| Suitable for gas concrete | yes |
| Suitable for hexagonal wood screw | no |
| Halogen-free | yes |
| With edge | no |
| With bolts | no |
| Mounting temperature, max. | 60 °C |
| Min. mounting temperature | 5 °C |
| ROHS-conformant | yes |
| Temperature-resistance, max. | 60 °C |
| Temperature resistance, min. | -20 °C |
| Suitable for material | Calcareous sandstone Porous concrete Concrete Gas concrete Full brick Hollow brick |
| Mounting type, anchor, tie | Push-through mounting |

### Loads

| | |
|---|---|
| Breaking load lime sandstone | 400 N |
| Safe working load concrete | 175 N |
| Safe working load vertically perforated brick | 130 N |
| Safe working load lime sandstone | 175 N |
| Breaking load concrete | 400 N |
| Breaking load vertically perforated brick | 300 N |