


# Technical data sheet

## Add-on tee 110 A2

Item number: 6042351



Add-on tee for the creation of a horizontal branch or cross-over, fitting for lock and screw-on cable trays of side height 110 mm. Screwless mounting with double clamps or screw connection with FRS truss-head screws and M6 combination nuts. Can be used indoors and outdoors. Fastening material must be ordered separately.



**A2** Stainless steel

**2B** Bright, treated

### Master data

|                                    |                          |
|------------------------------------|--------------------------|
| Item number                        | 6042351                  |
| Type                               | RAA 140 A2               |
| Description 1                      | Add-on tee               |
| Description 2                      | for cable tray           |
| Manufacturer                       | OBO                      |
| Dimension                          | 110x400                  |
| Colour                             | stainless steel          |
| Material                           | Stainless steel 1.4301   |
| Surface                            | Bright, treated          |
| Surface standard                   |                          |
| Smallest sales unit                | 1                        |
| Unit of quantity                   | Piece                    |
| Weight                             | 84.3 kg                  |
| Weight unit                        | kg/100 pc.               |
| CO2 Footprint (GWP) Cradle-to-Gate | 7,2353 kg CO2e / 1 Piece |


# Technical data sheet

## Add-on tee 110 A2

Item number: 6042351



### Dimensions



|                 |        |
|-----------------|--------|
| Width           | 400 mm |
| Height          | 110 mm |
| Plate thickness | 1 mm   |
| Dimension B     | 400 mm |

### Technical data

|                                         |                      |
|-----------------------------------------|----------------------|
| Departing width                         | 400 mm               |
| Connector version                       | Integrated connector |
| Maintain electrical functions           | no                   |
| Material thickness, floor plate         | 1 mm                 |
| NATO hole pattern                       | no                   |
| ROHS-conformant                         | yes                  |
| Rustproof steel, pickled                | no                   |
| Permitted temperature range, max.       | 120 °C               |
| Permitted temperature range, min.       | -20 °C               |
| Wide-span version                       | no                   |
| Type of connector, cable support system | screwed/clamped      |
| Recommended quantity of bolts           | 22 St.               |
| Rail thickness                          | 1.25 mm              |