


Technical data sheet

UDHOME2 floor socket, without floor covering recess, freely equippable, brass, decorative plate: oriental
Item number: 7368265



Square floor socket for use in dry-care cavity and screed floors. Installation housing with pre-marked insertion openings for pipes (M20/M25). Cover adjustable to top edge of floor covering using four height-adjustment supports. The minimum installation depth is 100 mm, the height-adjustment range 35 mm. Frame and cover made of brass and visible in the floor covering. Cover with Oriental decorative plate. Empty housing for up to 2 Modul 45® devices in the mounting support and 2 data sockets in the optional data technology support.





Master data		
Item number	7368265	
Type	UDHOME2 GM D2	
Description 1	Floor socket	
Description 2	unequipped, Oriental	
Manufacturer	OBO	
Dimension	140x140x110	
Smallest sales unit	1	
Unit of quantity	Piece	
Weight	220 kg	
Weight unit	kg/100 pc.	
CO2 Footprint (GWP) Cradle-to-Gate	10,3659 kg CO2e / 1 Piece	

Technical data sheet

UDHOME2 floor socket, without floor covering recess, freely equippable, brass, decorative plate: oriental
Item number: 7368265



Dimensions



Length	140 mm
Width	140 mm
Height	100 mm

Technical data

Number of installable devices	2
Cover version	Square
Cable outlet version	Swivellable cord outlet
Equipment	Empty housing
Floor covering protection frame	no
Floor care	Dry
Cover version	Decorative plate sample
Seal installation option	no
Application when used	6.101.1 Dry floor care
Application when unused	6.101.1 Dry floor care
Floor height, max.	135 mm
Floor height, min.	100 mm
Suitable for raised floor installation	yes
Suitable for screed-flush closed underfloor ducts	no
Suitable for screed-covered underfloor ducts	no
Suitable for cavity floor installation	yes
Suitable for wet care	no
Suitable for underfloor ducts	no
Device support to accept mounting boxes	no
With floor covering recess	no
Nominal size for device installation units	2
Standard	EN 50085-2-2
Frame version	Floor covering contact edge
ROHS-conformant	Exempt
Protection rating (IP) when used	IP20
Protection rating (IP) when unused	IP40
Protection rating IK code	IK10

Technical data sheet

UDHOME2 floor socket, without floor covering recess, freely equippable, brass, decorative plate: oriental
Item number: 7368265



Technical data

Heavy-duty version	no
Vertical load, large area	to 15,000 N
Vertical load, small area	to 3,000 N
Approvals	VDE
Opening mechanism	Handle